US009409179B2

(12) **United States Patent**
Ueda et al.

(10) **Patent No.: US 9,409,179 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **PULVERIZING APPARATUS AND PULVERIZING METHOD**

(75) Inventors: **Shigehisa Ueda**, Tokyo (JP); **Kazuo Noda**, Tokyo (JP)

(73) Assignee: **SUMITOMO BAKELITE COMPANY LIMITED**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 343 days.

(21) Appl. No.: **13/579,309**

(22) PCT Filed: **Feb. 21, 2011**

(86) PCT No.: **PCT/JP2011/053699**

§ 371 (c)(1),
(2), (4) Date: **Aug. 16, 2012**

(87) PCT Pub. No.: **WO2011/118310**

PCT Pub. Date: **Sep. 29, 2011**

(65) **Prior Publication Data**

US 2012/0318896 A1 Dec. 20, 2012

(30) **Foreign Application Priority Data**

Mar. 26, 2010 (JP) 2010-073419

(51) **Int. Cl.**
B02C 4/02 (2006.01)
B02C 4/32 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ... ***B02C 4/02*** (2013.01); ***B02C 4/32*** (2013.01); ***B02C 4/44*** (2013.01); ***B29B 13/10*** (2013.01)

(58) **Field of Classification Search**
CPC B02C 4/30; B02C 4/44; B02C 4/02; B02C 4/32; B02C 17/1875; B02C 17/188; B02C 19/186; B02C 23/24; B02C 23/26; B29B 9/04; B29B 13/10
USPC 241/38, 65–67, 227, 235, 293
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

153,325 A * 7/1874 Evans et al. 241/67
1,564,171 A * 12/1925 Brown 241/67
(Continued)

FOREIGN PATENT DOCUMENTS

GB 640866 * 8/1950 ..... B02C 4/44
JP 54-72565 A 6/1979
(Continued)

OTHER PUBLICATIONS

International Search Report issued in PCT/JP2011/053699 mailed Mar. 15, 2011.
(Continued)

Primary Examiner — Faye Francis
(74) *Attorney, Agent, or Firm* — Birch, Stewart, Kolasch & Birch, LLP

(57) **ABSTRACT**

A pulverizing apparatus for pulverizing a hard resin composition has a pulverizing mechanism having a pair of rollers arranged parallel to one another, these rollers pulverizing the hard resin composition by pressuring the hard resin composition between the rollers and a cooling device for cooling the hard resin composition during the hard resin composition being pulverized. Each of the rollers has a cylindrical shape with a hollow portion and the cooling device is configured to supply a coolant into the hollow portion of each of the rollers. The coolant flows in the hollow portion of each of the rollers in a longitudinal direction of each of the rollers. The cooling device has facilitating members respectively inserted into the hollow portions of the rollers.

9 Claims, 7 Drawing Sheets